




HASMAG

AIR DRYERS

Refrigerated Air Dryers



Accessories



Features:

Power Saving
Maintenance Free Operations
Low Pressure Drop
Noise Less Working
Easy to Operate
Continues Duty

Specifications

Capacity Cfm	HM 20	HM 30	HM 40	HM 50	HM 60	HM 80	HM 100	HM 125	HM 150	HM 200	HM 250	HM 300
Working Pressure Kg/cm ²	16	16	16	16	16	16	16	16	16	16	16	16
Pressure Drop Kg/cm ²	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Air Inlet Temp oC	45	45	45	45	45	45	45	45	45	45	45	45
Air Inlet/Outlet Connection (Bsp)	1/2"	1/2"	1/2"	1/2"	1"	1"	1 1/2"	1 1/2"	1 1/2"	1 1/2"	1 1/2"	1 1/2"
Auto Drain Outlet (Bsp)	1/2"	1/2"	1/2"	1/2"	1/2"	1/2"	1/2"	1/2"	1/2"	1/2"	1/2"	1/2"
Refrigerant	R134 A	R134 A	R134 A	R134 A	R134 A	R134 A	R134 A	R134 A	R 22	R 22	R 22	R 22
Power Supply	AC 220 V	AC 220 V	AC 220 V	AC 220 V	AC 220 V	AC 220 V	AC 220 V	AC 220 V	AC 220 V	AC 220 V	AC 220 V	AC 220 V
Power Consumption Kw	0.19	0.19	0.4	0.4	0.4	0.6	0.6	0.6	1	1	1.7	1.7
Pressure Dew Point oC	4	4	4	4	4	4	4	4	4	4	4	4
Atmospheric Dew Point C	(-) 22	(-) 22	(-) 22	(-) 22	(-) 22	(-) 22	(-) 22	(-) 22	(-) 22	(-) 22	(-) 22	(-) 22
Length (mm)	500	500	500	500	550	550	750	750	750	750	750	750
Height (mm)	615	615	615	615	800	800	990	990	990	990	990	990
Width (mm)	400	400	400	400	525	525	700	700	700	700	700	700
Width	45	45	45	45	80	90	120	120	120	120	140	140

**Hasmag Equipments Pvt. Ltd**

#15, 1st Main, 9th Cross
W C R, Mahalakshmpuram,
Bengaluru - 560086
Tel : (080) 23498509
E-mail : sales@hasmag.com
Website: www.hasmag.com

Distributed by :

